

LC Duplex Optical Fiber Adaptors

V.3.2

Description

FiberFab offers a range of quality LC adaptors which have high precision alignment sleeves for improved reliability and better reconnectability. The LC adaptors come with ceramic sleeves for singlemode and phosphor bronze sleeves for multimode. The housing is available in different colors with options for flange or flangeless body and metal or inbuilt clips.

Features


- ▶ Complies with IEC 61754-20
- ▶ High precision alignment sleeve
- ▶ Low insertion loss and high reconnectability
- ▶ RoHS, REACH SvHC compliant
- ▶ Also available in simplex and quad adaptors

Applications

- ▶ Telecommunications networks
- ▶ CATV, LAN, MAN and WAN application
- ▶ Data processing networks
- ▶ Cable television
- ▶ Fiber-To-The-Home
- ▶ Premises distribution

Technical Specification

	CERAMIC	PHOSPHOR BRONZE	CONFORMANCE
Insertion Loss (Typ)	0.1 dB	0.15 dB	IEC 61300-3-4
Mating Durability	500		IEC 61300-2-2
Receptacle Retention Force	1N - 2.5N		IEC 61754-20
Operating Temperature	-25 to +70, 12 cycles		IEC 61300-2-22



Ordering Information

MODE	TYPE	COLOUR	PART NO. DUPLEX	CONFIGURATION
SM	APC	GREEN	LCAPCUDGREEN	
SM	PC	BLUE	LCDPXBLUE	Flange with two holes and
MM	PC	BEIGE	LCDPXBEIGE	SC Simplex footprint with
MM	PC	AQUA	LCDPXAQUA/S	metal clips
MM	PC	ERIKA VIOLET	LCDPXEVS	

Part numbers for other style adaptors available on request

